

Application No. 10/613,556
Response to Office Action

Customer No. 01933

Listing of Claims:

Claims 1-8 (Canceled).

9. (New) A service vehicle comprising:

a vehicle main body;

an upper swing body mounted on the vehicle main body and
adapted to turn within a width of the vehicle main body;

5 a work implement; and

a downsizing device for reducing a size of a seat-side block
adjacent to a seat on the upper swing body;

wherein the downsizing device comprises a bubble remover for
removing bubbles in a hydraulic fluid for driving the work

10 implement.

10. (New) The service vehicle according to claim 9, wherein
a step section, which defines a path from the seat to outside of
the vehicle, is provided in front of the seat-side block so as to
define a path from the seat to outside of the vehicle.

11. (New) The service vehicle according to claim 9, further
comprising a cab which is provided on the upper swing body so as
to cover the seat;

Application No. 10/613,556
Response to Office Action

Customer No. 01933

5 wherein the work implement is provided substantially at a center portion of a front side of the upper swing body, and the work implement is tiltable toward the seat past a fitting section which connects the work implement to the upper swing body.

12. (New) The service vehicle according to claim 9, wherein the bubble remover is installed within a hydraulic tank which contains the hydraulic fluid.

13. (New) A service vehicle comprising:

a vehicle main body;

an upper swing body mounted on the vehicle main body and adapted to turn within a width of the vehicle main body; and

5 a downsizing device for reducing a size of a seat-side block adjacent to a seat on the upper swing body;

wherein the downsizing device comprises a variable capacity tank.

14. (New) The service vehicle according to claim 13, wherein a step section, which defines a path from the seat to outside of the vehicle, is provided in front of the seat-side block so as to define a path from the seat to outside of the vehicle.

Application No. 10/613,556
Response to Office Action

Customer No. 01933

15. (New) The service vehicle according to claim 13,
further comprising:

a cab which is provided on the upper swing body so as to
cover the seat; and

5 a work implement which is connected to the upper swing body
at a fitting section which is provided substantially at a center
portion of a front side of the upper swing body;

wherein the work implement is tiltable toward the seat past
the fitting section.

16. (New) The service vehicle according to claim 13,
wherein the variable capacity tank is attached to a cover of the
seat-side block.

17. (New) A service vehicle comprising:

a vehicle main body;

an upper swing body mounted on the vehicle main body and
adapted to turn within a width of the vehicle main body; and

5 a downsizing device for reducing a size of a seat-side block
adjacent to a seat on the upper swing body;

wherein the downsizing device comprises a hydraulic tank
which includes a plurality of tanks.

Application No. 10/613,556
Response to Office Action

Customer No. 01933

18. (New) The service vehicle according to claim 17, wherein the plurality of tanks comprises a variable capacity tank.

19. (New) The service vehicle according to claim 18, wherein the variable capacity tank is attached to a cover of the seat-side block.

20. (New) The service vehicle according to claim 17, wherein a step section, which defines a path from the seat to outside of the vehicle, is provided in front of the seat-side block so as to define a path from the seat to outside of the vehicle.

21. (New) The service vehicle according to claim 17, further comprising:

a cab which is provided on the upper swing body so as to cover the seat; and

a work implement which is connected to the upper swing body at a fitting section which is provided substantially at a center portion of a front side of the upper swing body;

wherein the work implement is tiltable toward the seat past the fitting section.